



DIMENSIONS AND FEATURES						PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	h min.-max.	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
2.75	2.75-2.85	6.64-7.00	0.56-0.64	0.72-0.85	0.157		100000	
3.60	3.60-3.72	8.64-9.00	0.95-1.05	1.12-1.30	0.416		35000	
4.55	4.55-4.67	10.57-11.00	1.14-1.26	1.35-1.55	0.741		17500	
5.50	5.50-5.62	13.57-14.00	1.43-1.57	2.30-2.60	1.409		9000	
7.40	7.40-7.55	17.57-18.00	1.91-2.09	2.80-3.10	3.160		4000	
9.30	9.30-9.45	22.48-23.00	2.46-2.54	3.30-3.60	6.824		1750	

Dimensions in mm

Technical details:

Hardness of material: 420 - 510 Hv.

Tightening couples: see table.

Chemical analysis of raw material: see table.

Sorted out material to prevent the presence of foreign parts.

Anticorrosion surface covering:

Dry and clean surface.

Features and specific use:

Washer to be used only for preassembling with metric pitch screws.